Communications & Power Industries CCTWT

The VTC-5764C pulsed-coupled cavity TWT covers 5.25 GHz to 5.75 GHz with 200 kW peak output power, 1.0% duty cycle. This device has a non-intercepting grid pulsed and single stage depressed collector to achieve 47 dB gain.

Custom configurations are also available. These variations in the performance and configuration include: cooling method (affects average power level), mechanical configuration, electrical and RF connections, & multiple stage depressed collector.

Contact us at MPPMarketing@cpii.com or call us at +1 650-846-2800.

Typical Operating Parameters

PARAMETER Cathode Voltage	MIN -50	MAX -47	UNITS kV
Cathode Current		16	а
Heater Voltage	8	10	V
Heater Current		10	Α
Collector Voltage	37	40	kV
Grid Bias Voltage	-850	-750	V
Grid Pulse Voltage	800	1000	V
RF Drive Power		1.0	W
Pulse Width		100	μsec
Duty Cycle		1.0	. %
Cooling Flow Rate	4.0		gpm
Pressure Drop		50	psig
Weight		60	lbs
Dimensions		8 X8X 44	inches

FEATURES:

- 5.25 GHz to 5.75 GHz
- 200 kW Peak output power
- 1.0% Duty cycle
- Non-intercepting grid pulsed
- 47 dB gain
- Single stage depressed collector
- Forced liquid cooled
- PPM focused
- Coaxial input, WR 187 waveguide output

BENEFITS:

- Efficient
- Bandwidth
- Over 40 years of technical expertise

APPLICATIONS:

Ground radars

