

Coupled Cavity TWT Transmitters

Communications & Power Industries CCTWT Transmitters



CPI Beverly Microwave Division manufactures CCTWT Transmitters for search and rescue radar, and G/MTI radars.

With a history of producing high quality products, we can help you with your coupled cavity TWT transmitter.

Contact us at BMDMarketing@cpil.com or at call us at +1 978-922-6000.

Typical Operating Parameters

Item	Frequency	Peak Power	Duty
Air Cooled	X - Band	15 KW	4%
Oil Cooled	X - Band	17 KW	6%
Water Cooled	C - Band	60 KW	5%

FEATURES:

- X-Band: 15 kW peak power, 4% duty, air cooled
- X-Band: 17 kW peak power, 6% duty, oil cooled
- C-Band: 60 kW peak power, 5% duty, water cooled

BENEFITS:

- Compact and rugged construction for use in difficult environments
- Excellent phase noise performance for MTI radar
- Excellent performance for all pulse wave forms
- Remote control via simple interface
- Built in test (BITE)

APPLICATIONS:

- Shipboard radars
- Airborne radars
- Ground based radars



Beverly Microwave Division
150 Sohler Road
Beverly, Massachusetts
USA 01915

tel +1 978-922-6000
email BMDMarketing@cpil.com
fax +1 978-922-8914
web www.cpii.com

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI. 6/20