

VTC-5767A Pulsed Coupled Cavity TWT

The VTC-5767A pulsed-coupled cavity TWT covers 5.4 GHz to 5.9 GHz with 20 kW peak output power, 2.5 % duty cycle. This device has a non-intercepting grid pulsed and single stage depressed collector to achieve 43 dB gain.

Custom configurations are also available. These variations in the performance and configuration include: cooling method (affects average power level), mechanical configuration, electrical and RF connections, & multiple stage depressed collector.

Features

- 5.4 GHz to 5.9 GHz
- 20 kW PEAK OUTPUT POWER
- 2.5% DUTY CYCLE
- NON-INTERCEPTING GRID PULSED
- 43 dB GAIN
- SINGLE STAGE DEPRESSED COLLECTOR
- FORCED AIR COOLED
- PPM FOCUSED
- COAXIAL INPUT, WR 187 WAVEGUIDE OUTPUT

Typical Operating Parameters

PARAMETER	MIN	MAX	UNITS
Cathode Voltage	-26	-24	kV
Cathode Current	---	6	a
Heater Voltage	8	10	V
Heater Current	---	5	A
Collector Voltage	18	21	kV
Grid Bias Voltage	-450	-350	V
Grid Pulse Voltage	250	400	v
RF Drive Power	---	1.0	W
Pulse Width	---	30	μsec
Duty Cycle	---	2.5	%
Cooling Flow Rate	4.0	---	lbm/min
Pressure Drop	---	4.0	In H ² O
Weight	---	45	lbs
Dimensions	---	8 DIA X 40 LG	inches

The values listed above represent specified limits for the product and are subject to change. The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.

For additional information on CPI MPP products contact:

CPI MPP, Coupled Cavity TWT Operation - 3120 Hansen Way, Palo Alto, CA 94303-0750
 Phone: 650-846-3073, Fax: 650-857-1708, Email: marketing@mpp.cpii.com, www.cpii.com/mpp