

50 W CW Rack-Mount TWTA

RF Output Power From 26.5 to 40.0 GHz

Provides 40 W CW at the flange.

Easy to Use and Versatile

Extensive diagnostic capability. Automatic output power control. Time stamped event log. Automatic filament shutdown. Manual override control. Dual communications interfaces. Continuous RF attenuator adjustment in 0.1 dB steps.

Ruggedly Built

Meets MIL-STD-810E.

Global Applications

Meets International Safety Standard EN61010 and Electromagnetic Compatibility 2004/108/EC.

Worldwide Support

Backed by over 35 years of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.



Model TE01AI-C

50 watt S/C-band TWTA
for EMC/EMI Test Applications

OPTIONS

- RF Input Attenuator
- Gain Variation Equalizer
- Integral Linearizer
- Mounting Configurations
- Low Gain (remove SSIPA)
- Others Available Upon Request
- Ethernet Interface



45 River Drive
Georgetown, Ontario, Canada L7G 2J4
tel: +1 (905) 702-2228
fax: +1 (905) 877-5327
e-mail: marketing@cmp.cpii.com
website: www.cpii.com/emc

50 W K-Band Rack Mount TWTA

Specification	Model TE01AI-C
Frequency	26.5 to 40.0 GHz
Output Power (min.), TWT	50 W CW
Output Power (min.), Flange	40 W CW
Bandwidth	13.5 GHz
Gain	46 dB typ. at rated power output
RF Level Adjust Range	0 to 20 dB
Gain Stability	±0.25 dB/24 hr max. (after 30 minute warmup and at constant drive and temperature)
Gain Variation	±6 dBc max. (±3 dBc max. with optional gain variation equalizer)
VSWR	Input Output Load
	2.0:1 max. 2.5:1 typ. 2.0:1 max. without damage
Noise and Spurious	-50 dBc typ. excluding harmonics
Prime Power	100 to 264 VAC single phase, 2 wire, 47 to 63 Hz
Power Consumption	800 VA nom.
Inrush Current	200%
Operating Temperature	-10°C to +50°C (derate by 1.9°C per 1,000 ft. above sea level)
Non-Operating Temperature	-40°C to +70°C
Relative Humidity	95% non-condensing
Operating Altitude	10,000 ft above sea level (3,048 m)
Non-Operating Altitude	50,000 ft above sea level (15,240 m)
Vibration	MIL-STD-810E, Method 514.4, Procedure 1, Category 1
Shock	10 g, 11 ms half sine
Acoustic Noise	<68 dBA max. at 1 meter
Air Flow	100 cfm
Cooling	Forced air, 2.0" clearance required
Input RF Connector	2.92 mm Type K Female
Output RF Connector	WR-28
Dimensions	5.2" H x 19.0" W x 24.0" L (133 x 483 x 610 mm)
Weight	65 lbs (29.5 kg) nom.