

750W Outdoor TWT Amplifier

for Satellite Communications

DBS-Band

The T07DO

750 Watt TWT Medium Power Amplifier — high efficiency in an environmentally sealed compact package designed for outdoor operation



Plays in the Rain

Provides 750 watts of power in a rugged and compact weatherproof package, digital ready, for wideband, single- and multi-carrier satellite service in the 17.3-18.4 GHz frequency band. Ideal for transportable and fixed earth station applications.

Cost Effective and Efficient

Mounting at the antenna improves performance through minimized cable losses and saves cost in system design. Employs a high efficiency, dual-depressed collector helix traveling wave tube, reducing operating costs.

Reliable

Designed and built to survive in extremely adverse environmental conditions and features increased cooling margin for longer life.

Simple to Operate

User-friendly microprocessor-controlled logic with integrated Ethernet computer interface. Digital metering, pin diode attenuation and optional integrated linearizer for improved intermodulation performance.

Easy to Maintain

Modular design and built-in fault diagnostic capability via remote monitor and control.

Global Applications

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2004/108/EC and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements.

Worldwide Support

Backed by over three decades of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes sixteen regional factory service centers.

satcom  **division**

811 Hansen Way
P.O. Box 51625, Palo Alto, CA 94303

tel: +1 (650) 846-3803
fax: +1 (650) 424-1744

e-mail: satcommarketing@cpil.com
www.cpii.com/satcom

DBS-Band

750W Outdoor TWT Amplifier

- OPTIONS:**
- *Integral Linearizer*
 - *Remote Control Panel*
 - *Redundant and Hybrid Power Combined Systems*
 - *Integral L-Band Block Upconverter (BUC)*
 - *Integrated switch control and drive (1:1 or 1:2)*
 - *Computer Interface: Ethernet Interface (standard) or RS422/485 (optional)*
 - *Inlet Air Filter*

SPECIFICATIONS, T07DO

Electrical

Frequency	17.3 to 18.4 GHz
Output Power	
TWT	750 W min. (58.75 dBm)
Flange	630 W min. (58.00 dBm)
Bandwidth	1100 MHz
Gain	70 dB min.
RF Level Adjust Range	0 to 30 dB typ.
Gain Stability	
At constant drive & temp.	±0.25 dB/24hr max. (after 30 min. warmup)
Over temp., constant drive	±0.75 dB over ±10°C
Small Signal Gain Slope	±0.02 dB/MHz max.
Small Signal Gain Variation	
Across any 80 MHz band	1.0 dB pk-pk max.
Across the 1100 MHz band	4.0 dB pk-pk max.
Input VSWR	1.3:1 max.
Output VSWR	1.3:1 max.
Load VSWR	
Continuous operation	2.0:1
Full spec compliance	1.5:1
Operation without damage	Any value
Phase Noise	
IESS Phase Noise Profile	10 dB below mask
AC fundamentals	-42 dBc (IESS-308 by 12 dB)
Sum of spurs (370 Hz to 1 MHz)	-50 dBc
AM/PM Conversion	2.5°/dB max. for a single-carrier at 7 dB below rated power
Harmonic Output	-60 dBc at rated power, second and third harmonics
Noise and Spurious	<-150 dBW/4 kHz, below 12.75 GHz <-65 dBW/4 kHz, 17.3 to 18.4 GHz <-105 dBW/4 kHz, 18.9 to 26.0 GHz <-125 dBW/4 kHz, 26.0 to 40.0 GHz
Intermodulation	-24 dBc or better with two equal carriers at total output power level of 130 W; -26 dBc at 260 W output power from 17.3 to 17.8 GHz with linearizer; -25 dBc at 260 W output power from 17.3 to 18.1 GHz with linearizer; -24 dBc at 260 W output power from 17.3 to 18.4 GHz with linearizer

Electrical (continued)

Group Delay	0.01 ns/MHz linear max.
(in any 80 MHz band)	0.001 ns/MHz sq. parabolic max. 0.5 ns pk-pk ripple max.
Primary Power	
Voltage	Single phase, 208-240 VAC ±10%
Frequency	47-63 Hz
Power Consumption	2.7 kVA max. 2.3 kVA typ. at 3 dB backoff
Power Factor	0.95 min.
Inrush Current	200% max.

Environmental (Operating)

Ambient Temperature	-40°C to +55°C operating in direct sunlight (to 60°C optional); -40°C to +60°C operating out of direct sunlight; -40°C to +75°C non-operating
Relative Humidity	100% condensing
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft., operating; 50,000 ft., non-operating
Shock and Vibration	20 G peak, 11 msec, 1/2 sine; 2.1 G rms, 5 to 500 Hz.
Acoustic Noise	68 dBA (as measured at 3 ft.)
Heat Dissipation	2000 W max.

Mechanical

Cooling (TWT)	Forced air with integral blower
RF Input Connection	Type SMA Female
RF Output Connection	WR-62 waveguide flange, grooved, threaded UNC 2B 6-32
RF Output Monitor	Type SMA female
Dimensions (W x H x D)	12.75 x 11.5 x 22.25 in. (324 x 292 x 566 mm)
Weight	79 lbs (35.9 kg) max.



For more detailed information, please refer to the corresponding CPI Technical Description.

Note: Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.

