

## For Satellite Communications Uplink Applications

Provides 1250 watts of CW power in a compact, 9 RU package, digital ready, for satellite uplink service in Ku-band. More powerful and 40% more efficient than comparable GaN SSPAs at Plin.

### Touchscreen Graphical Interface

State of the art touchscreen control/display with both amplifier and/or system level control capabilities. Includes fault logs, parameter trending and scopescreen for monitoring performance. Internal switch control eliminates need for external controllers.

### Simple to Operate

User-friendly microprocessor-controlled logic with integrated computer interface, Ethernet interface, digital metering, pin diode attenuation, optional integrated linearizer for improved intermodulation performance, and BUC option for use with L-band modems.

### Easy to Maintain

Modular design with built-in fault diagnostic capability providing convenient and clearly visible indicators for easy maintainability in the field. A USB port is available for uploading new firmware and system configurations, as well as downloading logs and system configurations for cloning to other units.



CPI 1250 W Ku-band TWTA,  
Model T9UI

### OPTIONS:

- Remote control panel
- Redundant and hybrid power combined systems
- Integrated switch control and drive
- Integral linearizer
- Integral block upconverter (BUC) or dual band BUC - contact CPI for specifications.
- External receive band reject filter
- Ethernet interface
- TWT LifeExtender/LifePredictor
- Uplink power control

Quality Management  
System - ISO 9001:2015



### Meets Global Requirements

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2014/30/EU and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements. CE Marked.

### Worldwide Support

Backed by over 40 years of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.

| Specification   | Model T9UI 1250 W Ku-band TouchPower TWTA  |
|---|--|
| Output Frequency  | 13.75 to 14.50 GHz   |
| Output Power (min.)<br>TWT CW Power<br>Flange CW Power                    | 1250 W (60.97 dBm) min.<br>1100 W (60.41 dBm) min.   |
| Bandwidth   | 750 MHz  |
| Gain  | 70 dB min.   |
| RF Level Adjust Range   | 0 to 30 dB (via PIN diode attenuator) typ, 0.1 dB steps  |
| Gain Stability  | ±0.25 dB/24 hour max,max. at constant drive and temperature, after 30 minute warmup<br>±0.1 dB typ. over operating temperature range, constant drive   |
| Small Signal Gain Slope   | ±0.02 dB/MHz max.  |
| Small Signal Gain Variation   | 1.0 dB pk-pk max. across any 80 MHz (1.5 dB pk-pk max. with linearizer option);<br>3.0 dB pk-pk max. across the 750 MHz band (4.0 dB pk-pk with optional linearizer)   |
| Input/Output VSWR   | 1.3:1 max./1.3:1 max.  |
| Load VSWR   | 1.5:1 for full spec. compliance; any value operation without damage; 2.0:1 continuous operation  |
| Phase Noise   | 12 dB below IESS-308/309 phase noise profile; -50 dBc AC fundamentals related; -47 dBc sum of spurs;<br>Prime power AC line unbalance not to exceed 3%. Excess imbalance may cause an increase in residual RF noise (AM, FM and PM). Phase noise increase is typically 2.5 dB/% imbalance. |
| AM/PM Conversion  | 2.5°/dB max. with optional linearizer, for a single carrier at 57 dBm output power<br>(6.0°/dB max. without linearizer)  |
| Harmonic Output   | -60 dBc max.   |
| Noise Density   | <-150 dBW/4 kHz from 10.0 to 12.7 GHz<br><-70 dBW/4 kHz in passband, <-65 dBW/4 kHz in passband with linearizer<br><-105 dBW/4 kHz from 18.0 to 26.0 GHz, <-125 dBW/4 kHz from 26.0 to 40.0 GHz  |
| Intermodulation - with respect to the sum of 2 equal carriers 5 MHz apart | -25 dBc at 270 W output power with no linearizer;<br>-25 dBc at 540 W output power with linearizer   |
| Spectral Regrowth   | -30 dBc at 1 symbol offset, 5.6 Msps, at 1000 W output power with linearizer   |
| Group Delay   | 0.01 ns/MHz linear max; 0.001 ns/MHz <sup>2</sup> parabolic max; 0.5 ns pk-pk ripple max.  |
| Primary Power   | Voltage: Three phase with neutral and ground, 200-240 VAC L-L ±10% OR 380 to 415 VAC L-L ±10%;<br>Frequency: 47-63 Hz ±10% five wire;<br>AC current harmonic content: less than 20%, primarily fifth and seventh harmonics.<br>Harmonics must be considered when choosing UPS sources.     |
| Power Consumption   | 4.9 kVA typ. at 1100 W output power  |
| Power Factor  | 0.92 min; 0.95 typ.  |
| Ambient Temperature   | 10°C to +50°C operating; -54°C to +71°C non-operating  |
| Relative Humidity   | 95% non-condensing   |
| Altitude  | 10,000 ft. with standard adiabatic derating of 2°C/1000 ft. operating; 50,000 ft. non-operating  |
| Shock and Vibration   | Designed for normal transportation environment per Section 514.4 MIL-STD-810E.<br>Designed to withstand 20g at 11 ms (1/2 sine pulse) in non-operating condition   |
| Cooling   | Forced air with integral blower. Maximum external pressure loss allowable: 0.25 inch water gauge.  |
| Connections   | RF Input: Type N Female;<br>RF output: WR75G waveguide flange, grooved, threaded, UNF 2B 6-32 holes;<br>RF output monitor: Type N Female   |
| M&C Interface   | Ethernet, Serial, SNMP, & USB  |
| Weight and Dimensions   | 155 lbs (70.5 kg) max. / 19 W x 15.75 H x 24 D inches (483 W x 400 H x 610 D mm)   |



**SMP Division**  
**Satcom Products**  
tel: +1 (669) 275-2744  
email: [satcommarketing@cpii.com](mailto:satcommarketing@cpii.com)  
web: [www.cpii.com/satcom](http://www.cpii.com/satcom)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

© 2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.