# For EMC/EMI and other instrumentation applications.

Provides a minimum of 250 watts of power in a 5 rack unit package, across the 8.0 to 18.0 GHz frequency range.

#### **Touchscreen Graphical Interface**

State of the art touchscreen interface with both amplifier and/or system level control capabilities. Includes fault logs, parameter trending and scopescreen for monitoring performance. Internal switch control eliminates need for external controllers.

#### Easy to Maintain

Modular design and built-in fault diagnostic capability with convenient and clearly visible indicators for easy maintainability in the field. A USB port is available for uploading new firmware and system configurations and downloading logs and system configurations for cloning to other units.

#### **Meets Global Requirements**

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2014/30/EU and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements. CE Marked.

### **Worldwide Support**

Backed by over 40 years of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.



CPI 250/320 W M-band TWTA, Model TZM6993J1

#### **OPTIONS:**

- Input isolator (-1 dB gain)
- Remote control panel
- 115 VAC external step-up transformer
- LifeExtender™/LifePredictor

Quality Management System - ISO 9001:2015





Specification	CPI Model TZM6993J1 250/320 W TouchPower TWTA	
Frequency	8.0 to 18.0 GHz	
Output Power (min.), TWT	320 W CW	290 W CW
Output Power (min.), Flange	250 W CW	225 W CW
Bandwidth	10.0 GHz	
Gain	53.5 dB min. at rated power output; 53.5 dB typ. at small signal	
RF Level Adjust Range	0 to 20 dB continuous	
Gain Stability	±0.25 dB/24 hr max. (after 30 minute warmup and at constant drive and temperature)	
Gain Variation	12 dB pk-pk over 6.0 GHz bandwidth, typ.	
VSWR Input Output Load	2.5:1 typ, 1.5:1 max. (with optional input isolator) 2.5:1 typ. 1.5:1 max. full spec compliance; 2.0:1 max. continuous operation; any value without damage	
Residual AM	-50 dBc below 10 kHz; -20[1.3 + log F (kHz)] dBc, 10 kHz to 500 kHz; -85 dBc above 500 kHz	
Phase Noise	Meets IESS 308/309	
Noise and Spurious	-50 dBc typ. excluding harmonics	
Harmonic Content	-3 dBc typ. at lower band edge	
Prime Power	220 to 240 VAC single phase ±10%, 47 to 63 Hz	
Radiated Immunity	10 V/m (for higher immunity levels, contact CPI)	
Power Consumption	2.6 kVA typ, 3.0 kVA max.	
Inrush Current	200%	
Ambient Temperature	-10°C to +40°C operating; -54°C to +71°C non-operating	
Relative Humidity	95% non-condensing	
Operating Altitude	10,000 ft above sea level (3,048 m), with standard adiabatic de-rating of 2° C per 1,000 feet; 40,000 ft non-operating	
Shock and Vibration	Designed to meet conditions normally encountered in the laboratory	
Acoustic Noise	65 dBA one meter from front panel	
Cooling	Forced air with integral blower. Rear air intake and exhaust	
Input RF Connector	Type SMA Female	
Output RF Connector	WRD-750	
RF Power Monitors	Type SMA Female, -50 dB nominal	
M&C Interface	RJ45 Ethernet, includes embedded GUI control (RS422/485, RS232 serial interface, GPIB optional)	
USB Port	Download/Upload software, logs	
Dimensions	19" W x 8.75" H x 26.0" L (483 x 222 x 661 mm)	
Weight	110 lbs (50 kg) nom.	
Safety	EN-60215	



## SMP Division Satcom Products

tel: +1 (650) 846-2900 email: satcommarketing@cpii.com web: www.cpii.com/satcom For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

@ 2020 Communications & Power Industries LLC. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.