

Communications & Power Industries Triode



The 3CW30,000H7 is a high-mu power triode designed for use as a zero bias Class B RF amplifier, Class C power amplifier or oscillator, or for voltage regulator service. Input of 48 kW is permissible up to 110 MHz. Plentiful reserve emission is available from its one kilowatt filament. Class B operation with zero bias grid bias offers circuit simplification by eliminating the bias supply.

FEATURES:

Maximum plate dissipation:	30,000 Watts
Maximum screen dissipation:	---
Maximum grid dissipation:	500 Watts
Frequency for max rating (CW):	110 MHz
Amplification factor:	200
Filament/cathode:	Thoriated Tungsten
Voltage:	6.3 Volts
Current:	160 Amps
Capacitance: Grounded cathode	
Input:	56.0 pF
Output:	0.2 pF
Feedthrough:	36.0 pF
Capacitance: Grounded grid	
Input:	56.0 pF
Output:	36.0 pF
Feedthrough:	0.2 pF
Cooling:	Water and Forced Air
Base:	Flexible Filament Leads
Air Socket:	---
Air Chimney:	---
Boiler:	---
Length:	20.60 in; 524.00 mm
Diameter:	6.75 in; 171.40 mm
Weight:	12.0 lb; 5.5 kg

BENEFITS:

- Worldwide brand name recognition
- Over 85 years technical expertise

APPLICATIONS:

- Industrial

Class of Operation	Type of Service	MAXIMUM RATINGS		TYPICAL OPERATION				
		Plate Voltage (Volts)	Plate Current (Amps)	Plate Voltage (Volts)	Screen Voltage (Volts)	Plate Current (Amps)	Drive Power (Watts)	Output Power (kiloWatts)
C	Grid driven RF power amplifier	8,000	5.0	7,000	---	4.0	430	21.3
AB	Cathode driven RF linear amplifier	8,000	6.0	7,000	---	5.0	1,540	24.2
A	Voltage regulator	28,000	6.0	---	---	---	---	---

With a history of producing high quality products, we can help you with your triode.

Contact us at MPPMarketing@cpii.com or call us at +1 650-846-2800. The data should be used for basic information only.

Formal, controlled specifications may be obtained from CPI for use in equipment design.



**Microwave Power
Products Division**
811 Hansen Way
Palo Alto, California
USA 94304

tel +1 650-846-2800
fax +1 650-856-0705
email MPPMarketing@cpii.com
web www.cpii.com/MPP

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC.
Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.