

## Communications & Power Industries Triode



The 3CX15,000H3 is a forced air cooled, ceramic/metal, medium-mu power triode designed primarily for use in industrial radio frequency heating services. Input of 56.2 kW is permissible up to 90 MHz. Plentiful reserve emission is available from its 1000 watt filament. The grid structure is rated at 500 watts making this tube an excellent choice for industrial service.

### FEATURES:

Maximum plate dissipation:	15,000 Watts
Maximum screen dissipation:	---
Maximum grid dissipation:	500 Watts
Frequency for max rating (CW):	90 MHz
Amplification factor:	20
Filament/cathode:	Thoriated Tungsten
Voltage:	6.3 Volts
Current:	160 Amps
Capacitance: Grounded cathode	
Input:	55.0 pF
Output:	1.4 pF
Feedthrough:	34 pF
Capacitance: Grounded grid	
Input:	--- pF
Output:	--- pF
Feedthrough:	--- pF
Cooling:	Forced Air
Base:	Flexible Filament Leads
Air Socket:	SK-1306
Air Chimney:	---
Boiler:	---
Length:	17.75 in; 450.80 mm
Diameter:	7.05 in; 179.10 mm
Weight:	13.0 lb; 5.9 kg

### BENEFITS:

- Worldwide brand name recognition
- Over 85 years technical expertise

### APPLICATIONS:

- Communications
- Industrial

Class of Operation	Type of Service	MAXIMUM RATINGS		TYPICAL OPERATION				
		Plate Voltage (Volts)	Plate Current (Amps)	Plate Voltage (Volts)	Screen Voltage (Volts)	Plate Current (Amps)	Drive Power (Watts)	Output Power (kiloWatts)
C	RF Industrial oscillator or amplifier	12,000	6.0	10,000	---	5.0	650	41.2

With a history of producing high quality products, we can help you with your triode.

Contact us at [MPPMarketing@cpii.com](mailto:MPPMarketing@cpii.com) or call us at +1 650-846-2800. The data should be used for basic information only.

Formal, controlled specifications may be obtained from CPI for use in equipment design.



**Microwave Power  
Products Division**  
811 Hansen Way  
Palo Alto, California  
USA 94304

tel +1 650-846-2800  
fax +1 650-856-0705  
email [MPPMarketing@cpii.com](mailto:MPPMarketing@cpii.com)  
web [www.cpii.com/MPP](http://www.cpii.com/MPP)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC.  
Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.