Reflector & Feed Electrical Anti-Icing System

Specifications

| CVCTCAA CITC | ADEDTUDE ADDUCATION | DACK COVED | WATTS OPERATING | | CURRENT | |
|----------------|----------------------|--------------|-----------------|---------|----------|----------|
| SYSTEM SIZE | APERTURE APPLICATION | BACK COVER | 120 VAC | 240 VAC | 120 VAC | 240 VAC |
| 1.2 M 0.6 f/d | Half Aperture | Half Cover | 217 | 239 | 1.8 amps | 1.0 amps |
| 1.2 M 0.8 f/d | Half Aperture | Full Cover | 310 | 309 | 2.6 amps | 1.3 amps |
| 1.8 M 0.6 f/d | Half Aperture | Half Cover | 477 | 536 | 4.0 amps | 2.2 amps |
| 1.8 M 0.8 f/d | Half Aperture | Half Cover | 558 | 559 | 4.7 amps | 2.3 amps |
| 2.4 M 2-Piece | Half Aperture | Half cover | 763 | 776 | 6.4 amps | 3.3 amps |
| 2.4 M 4-Piece | Half Aperture | 2 Quad Cover | 895 | 896 | 7.4 amps | 3.7 amps |
| 3.8 M 4-Piece | Half Aperture | 2 Quad Cover | N/A | 2354 | N/A | 9.8 amps |
| 0.74 M Ellip | Half Aperture | 2 Quad Cover | 163 | 2260 | 1.4 amps | 9.5 amps |
| 0.98 M 0.8 f/d | Half Aperture | Half Cover | 163 | N/A | 1.4 amps | N/A |
| 1.0 M 0.6 f/d | Half Aperture | Half Cover | 163 | N/A | 1.4 amps | N/A |
| 1.2 M 0.8 f/d | Half Aperture | Half Cover | 286 | N/A | 2.4 amps | N/A |

^{*}Other Sizes Available

The CPI Satcom & Antenna Technologies Inc. (CPI SAT) Anti-Iced Antennas have power densities of approximately 35 watts per sq. ft. of heated surface utilizing the "blanket" resistive wire technique.

The Moisture/Temperature version is an automatic system that will activate heaters when the temperature falls below about 38 degrees Fahrenheit (3 C.) and sufficient moisture is present to permit the formation of solid precipitants. These features are cost savings driven so that power is applied only when atmospheric conditions warrant.

Systems include a selector switch permitting the operator to energize the heaters at any time, or to disable (turn off) the automatic feature at discretion.

Systems with Temperature only controls activate heaters at about 38 degrees Fahrenheit and remain on until temperatures rise above 45 degrees Fahrenheit.

Contact us at CustomerCareSAT@cpii.com or call us at +1 770-689-2040

The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.



Satcom & Antenna Technologies Division

1700 NE Cable Drive Conover, NC USA 28613 +1 770-689-2040 1 888-874-7646 (In North America)

1 619-240-8480 (Outside North America)

CustomerCareSAT@cpii.com www.cpii.com

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design. © 2022 Communications & Power Industries LLC. Company proprietary: use and reproduction is strickly prohibited without written authorization from CPI.

©2022 Communications & Power Industries LLC. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI.